

Application Serial No: 10/644,549  
In reply to Office Action of 16 May 2005

Attorney Docket No. 84454

AMENDMENTS TO THE CLAIMS

1. (currently amended) An optical fiber coupler for connecting a first fiber optic element to a second fiber optic element, the coupler comprising:

a first fiber optic element extending in a first direction whereby to position a free end of said first fiber optic element in a selected zone;

a second fiber optic element extending into the selected zone from a direction generally opposite to the first direction to position a free end of said second fiber optic element in the selected zone and proximate the first fiber optic element free end; and

a cured optical grade epoxy resin body comprising the selected zone and enveloping the free ends of said fiber optic elements, wherein said body is provided with a cone-shaped end and a generally planar base end;

whereby to provide physical and optical connection between said first and second fiber optic elements.

Application Serial No: 10/644,549  
In reply to Office Action of 16 May 2005

Attorney Docket No. 84454

2. (original) The coupler in accordance with claim 1 wherein said first fiber optic element comprises a single fiber optic strand and said second fiber optic element comprises a plurality of fiber optic strands.

3. (canceled)

4. (currently amended) The coupler in accordance with claim [[3]] 1 wherein said first fiber optic element comprises a single fiber optic strand disposed in an apex of the cone-shaped end of said body and the single fiber optic strand extends through the apex and into said body.

5. (original) The coupler in accordance with claim 4 wherein said second fiber optic element comprises a plurality of fiber optic strands extending into said body through the base end.

6. (original) The coupler in accordance with claim 1 wherein said first and second fiber optic elements comprise at least one fiber optic strand and at least another fiber optic strand, respectively.

7. (original) The coupler in accordance with claim 6 wherein the free end of each of said at least one fiber optic strand of

Application Serial No: 10/644,549  
In reply to Office Action of 16 May 2005

Attorney Docket No. 84454

said first fiber optic element and the free end of each of said at least another fiber optic strand of said second fiber optic element are butt-end terminated.

8. (original) The coupler in accordance with claim 1 wherein at least one of said first and second fiber optic elements comprises a plurality of fiber optic strands, the positions to which the free ends of said first and second elements extend being spaced apart by a distance allowing a sufficient extent of diffusion of light in the optical grade epoxy resin therebetween to couple light between each strand of one of said first and second fiber optic elements with each strand of the other of said elements.

9. (original) The coupler in accordance with claim 5 wherein said plurality of fiber optic strands is arranged in a ring-like pattern about a central axis of the cone-shaped end of said body.

10. (original) A method for connecting a first fiber optic element to a second fiber optic element, the method comprising the steps of:

Application Serial No: 10/644,549  
In reply to Office Action of 16 May 2005

Attorney Docket No. 84454

providing a rigid elongated body having a cone-shaped end  
and an opposite circular and planar base end;

coating outer surfaces of the body other than the base end  
with a layer of mold making wax;

separating the body from the wax to provide a hollow wax  
housing having a cone-shaped end and an open base end;

providing a hole in an apex of the housing cone-shaped end;

inserting a first fiber optic element comprising a single  
fiber optic strand through the hole in a first  
direction into the wax housing to position a free end  
of the single fiber optic strand in the housing;

applying a sealant to the single strand at the housing apex  
hole;

inserting the second fiber optic element comprising a  
plurality of fiber optic strands into the wax housing  
through the open-base end from a direction generally  
opposite to the first direction to position free ends  
of the plurality of fiber optic strands in the housing

Application Serial No: 10/644,549  
In reply to Office Action of 16 May 2005

Attorney Docket No. 84454

and proximate the single fiber optic strand free end,  
the positions to which the free ends of said first and  
second element strands are inserted being spaced apart  
by a distance to allow a sufficient extent of  
diffusion of light in the optical grade epoxy resin  
therebetween to couple light between the strand of the  
first fiber optic element and each strand of the  
second of the fiber optic elements;

filling the wax housing with optical grade epoxy resin and  
permitting the resin to cure;

whereby to effect physical and optical connection between  
the first and second fiber optic elements; and

removing the wax housing from the resin.